

Atty Docket No.: JCLA6047

Serial No.: 09/750,819

A1
in
cluded

modulation (PCM) signal having n bits and then outputting a pulse width modulation (PWM) signal. The MPWM DAC comprises a converter circuit, a control device, a first output driver device, a second output driver device and an output device.

The converter circuit converts $(n-m)$ bits of the PCM signal into the PWM signal, wherein m is the number of the least significant bit (LSB) signal of the PCM signal and $n > m$. Each of the first output driver device and the second output driver has different number of output drivers, thereby the output PWM signal is a multi-level signal, rather than a two-level signal in the prior art.

In The Claims

/ Please amend independent claims 1 and 8 as follows

1. (Once Amended) A multi-level pulse width modulation (MPWM) digital-to-analog converter for receiving a pulse code modulation (PCM) signal having n bits and then outputting a pulse width modulation (PWM) signal, comprising:

A2
a converter circuit for receiving the PCM signal to convert $(n-m)$ bits of the PCM signal into the PWM signal, wherein m is the number of the least significant bit (LSB) signal of the PCM signal and $n > m$, and then generating a first input signal, a second input signal and an enabling signal;

a control device for receiving the enabling signal to generate a control signal;

Atty Docket No.: JCLA6047

Serial No.: 09/750,819

A2
a first output driver device having 2^{m1} output drivers ($m1 < n$) for receiving the first input signal and the control signal, and then outputting a first driving signal, wherein sum of output currents of the 2^{m1} output drivers is equal to a maximum output current of the first output driver device;

a second output driver device having 2^{m2} output drivers ($m2 < n$) for receiving the second input signal and the control signal, and then outputting a second driving signal, wherein sum of output currents of the 2^{m2} output drivers is equal to a maximum output current of the second output driver device; and

an output device for receiving the first and the second driving signals and then outputting the PWM signal;

wherein in response to the least significant bit (LSB) signal of the PCM signal, the control device selects and disables in a specified interval of each sampling cycle such that the output drivers the first and the second output driver devices are in a high impedance status, to control outputs of the first and the second output driver devices.

A3
8. (Once Amended) A multi-level pulse width modulation (MPWM) digital-to-analog converter for receiving a digital signal, wherein the digital signal comprises at least one modulated bit and at least one level bit and then outputs an analog modulated signal, comprising:

a converter circuit for receiving the digital signal and then converting the modulated bit into a first output signal, a second output signal, and the converter circuit outputting the first output signal, the second output signal and the level bit of the digital signal;

Atty Docket No.: JCLA6047

Serial No.: 09/750,819

A3
can include

a control device for receiving the level bit of the digital signal to generate a control signal;
a plurality of first output drivers for receiving the first input signal and the control signal,
and then outputting a first driving signal, wherein sum of output currents of the first output
drivers is equal to a maximum output current corresponding to the first driving signal;

a plurality of second output drivers for receiving the second input signal and the control
signal, and then outputting a second driving signal, wherein sum of output currents of the first
output drivers is equal to a maximum output current corresponding to the first driving signal; and

an output device for receiving the first and the second driving signals and then outputting
the analog modulated signal.